



D3875-1 FLOOR PROTECTOR (206B)

NOTES:

- 1) MATERIAL: MLEXS.118-90318-08 (LEXAN POLYCARBONATE, CLEAR, 0.118" THICK)
- 2) FINISH: NONE
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY WITH DART P/N "D3875-1" PER DART QSI 044 METHOD 6.4
- 7) WEIGHT: 3.81 lbs
- 8) TOOLING: THERMOFORM PER MOLD DT9475 PER QSI 022. TRIM PER MOLD.
- 9) MINIMUM MATERIAL THICKNESS AFTER FORMING IS 0.050" EXCEPT WHERE SHOWN
- 10) EDGE FLANGE MAY BE TRIMMED FOR FIT BY CUSTOMER, AS REQUIRED.

RELEASED
2013-04-18

B	19.5 WAS 18.6 MIN (ZN B3-1), 45.0 WAS 45.2 (ZN D6-1), 1.1 MIN. WAS 0.5 MIN. (ZN B8-1)	DB	13.04.09
A	NEW ISSUE	PH	09.01.29
REV.	DESCRIPTION	BY	DATE
DESIGN	DB	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	DB		
CHECKED	AP	DRAWING NO.	REV. B
MFG. APPR.	LF	D3875	SHEET 1 OF 1
APPROVED	MF	TITLE	SCALE
DE APPR.	MF	FLOOR PROTECTOR (206B)	NTS
DATE	13.04.09	COPYRIGHT © 2013 BY DART AEROSPACE LTD. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	